

AN ORDINANCE OF THE CITY COUNCIL OF THE CITY OF HUDSON, TEXAS, PROVIDING FOR MINIATURE, TRANSPORT- ABLE HOUSING (TINY HOMES); PROVIDING FOR A CONFLICTS RESOLUTION CLAUSE; PROVIDING A SEVERABILITY CLAUSE; PROVIDING A SAVINGS CLAUSE; PROVIDING A PENALTY OF FINE NOT TO EXCEED FIVE HUNDRED DOLLARS (\$500.00) FOR EACH OFFENSE; AND PROVIDING AN EFFECTIVE DATE.

WHEREAS it is in the best interest of the City of Hudson that the health, safety, and general welfare of the City be promoted by planning the orderly growth of the City; and

WHEREAS the City Council of the City of Hudson finds it to be in the best interest of the public safety, health, and general welfare to regulate the location of Tiny Houses within the City of Hudson and its ETJ; therefore,

BE IT ORDAINED BY THE CITY COUNCIL OF THE CITY OF HUDSON, TEXAS, THAT:

SECTION 1. DEFINITIONS

- 1. <u>"Building Official"</u>: City Building Official, City Fire Marshal, or other designated inspection authority of the City of Hudson.
- 2. <u>"Permit":</u> Written permit and or application issued by the City permitting the location, placement, alteration or extension of a Tiny Home under the provisions of this ordinance and regulations issued hereunder.
- 3. <u>"Tiny House Park"</u>: For purposes of this ordinance, the phrase "Tiny House Park" means a unified development located on the Property configured as a single lot undivided or divided but on which individual lease pads, along with common areas and open spaces area established, on which Pads are privately owned, and where more than two Tiny Houses may be placed on a track.
- 4. "Tiny House" Defined; Size and Construction Standards: For purposes of this ordinance, a "Tiny House" is defined as a principal residential dwelling that has a square footage of no less than two hundred forty (240) square feet and no greater than eight hundred (800) square feet, with said dwelling being with or without a permanent foundation, capable of being connected to available utilities including plumbing (water and sewer service), mechanical, natural gas, communications, and electrical systems. Tiny Houses constructed or otherwise located in the city shall be subject to the following requirements:

SECTION 2: BASIC TINY HOUSE REQUIREMENTS:

- 1. <u>Minimum Unit Size:</u> Each Tiny House shall have a minimum gross floor area of not less than two hundred forty (240) square feet.
- 2. <u>Minimum Sleeping Room Size:</u> In every Tiny House of two or more rooms, every room occupied for sleeping purposes by one occupant shall contain at least seventy (70) square feet of floor space.

- 3. <u>Width:</u> Each Tiny House must measure not less than twelve feet (12) and the total area shall be not less than two hundred forty (240) square feet.
- 4. **Restroom:** Each Tiny House shall have at least one restroom dedicated and capable of connecting to city utilities and discharging wastewater.
- 5. <u>Construction Standards:</u> In addition to the regulations set forth in this ordinance, every Tiny House located in the city, whether constructed in the city on a permanent foundation or constructed off-site and transported to the city, shall, at the time of application for a building permit or, if not building permit is required, certificate of occupancy, be constructed in accordance with:
 - A. All construction codes relating to residential dwelling units enacted by the City of Hudson that are deemed to be applicable to the structural stability and life safety requirements for a Tiny House as determined by the City of Hudson, Building Official and or designee; and,
 - B. <u>Appendix V, Tiny Houses to the International Residential Code</u>, as approved by the International Code Council (ICC) and amended by the City of Hudson a copy of which is attached hereto as **Exhibit "A"** and incorporated herein by reference.
- 6. **Foundation Platforms:** Tiny Houses located in the city shall be constructed with one of the following foundation platforms:
 - A. Conventional foundation platforms, such as concrete slab on grade, pier and beam, perimeter grade beam, and similar permanent foundation types shall be permitted, with such foundations being certified by a registered professional structural engineer as a condition of securing building permit approval.
 - 7. <u>Setbacks</u>: When located on a Pad, a Tiny House shall be set back not less than 10 feet (10') from the side and back property lines of the Property; provided, however, porches, awnings, and other additions attached to the Tiny House may project a distance of not greater than an additional three feet (3') beyond the foregoing setback. Not less than fifteen (15') feet from front property lines.
 - **8.** <u>Tiny Homes</u> may not be located in any subdivision in the City of Hudson nor in any subdivision in the City of Hudson's ETJ or connected to any City of Hudson Utilities located in any subdivision where the City provides utilities.

Exception: in the Rollingwood and Cripple Creek Subdivision with a variance granted by the City Council.

- 9. <u>Tiny Homes</u> after the application is reviewed and its relation to the present and anticipated land use and development is considered, and it also complies with this ordinance and any other applicable laws, codes, and regulations and ordinance, the permit may be issued for locations not in subdivisions. Only two living dwellings may be located on a tract of land (one Tiny Home in addition to an existing dwelling or two Tiny Homes) on a vacant tract or parcel of land.
- 10. <u>Tiny Home Parks.</u> It shall be unlawful for any person to locate a tiny home park within the city limits of the City of Hudson, Texas.

SECTION 4: PERMITS/ AND VARIANCES

- 1. **Permit required:** a permit is required to locate any Tiny Home in the City of Hudson and or its ETJ.
- 2. <u>Variance required</u> to locate a Tiny Home in the subdivisions of Rollingwood and Cripple Creek a variance is <u>REQUIRED for</u> all other Subdivisions it is **PROHIBITED**.
- 3. <u>Application Requirements for a Permit All Tiny Homes to be located in the City of Hudson or the City of Hudson's ETJ must complete an application for building on-site or being moved in. The application must include:</u>
 - a. Names and Address of Applicant.
 - b. Telephone Number.
 - c. Location, Legal Property Description, Block, Lot, and Platt where Tiny Home is to be located.
 - d. Dimensions of Tiny Home.
 - e. Description of Material being used.
 - f. Blueprints or Drawings showing the placement and identifying connections to City services including Water, Sewer, and Sanitation.
 - g. Photographs of the Tiny Home if available.
- 4. <u>Issuance of Permit</u>: in considering the application the City may take into consideration the proposed location of the Tiny House in relation to present and anticipated land use including development.
 - a. It must have a driveway.
 - b. It must have an assigned 911 address.
 - c. It must have skirting. constructed with fire-resistant skirting, with the necessary vents, screens, and/or openings that are installed within thirty (30) days after placement of the Tiny House on a pad or blocks.
 - d. It must be connected to City Utilities, sewer, sanitation, and water. No composting toilets are permitted.
 - e. It must comply with the International Building Code where required and all City ordinances.
 - f. It must have all inspections Building, Plumbing, Electrical, and Occupancy

SECTION 3. CONFLICTS. To the extent of any irreconcilable conflict with the provisions of this ordinance and other ordinances of the City of Hudson governing the use and development of the Property which are not expressly amended by this ordinance, the provisions of this ordinance shall be controlling. In the event there is an irreconcilable conflict within the text of this ordinance, including any exhibits attached hereto, relating to the applicable standard to be enforced, the strictest standard shall be controlling unless the City Council determines by approval of a motion or resolution that the less stringent standard is to apply.

SECTION 4. SEVERABILITY CLAUSE. Should any word, sentence, paragraph, subdivision, clause, phrase, or section of this ordinance, or of the Hudson Code of ordinances, as amended hereby, be adjudged or held to be void or unconstitutional, the same shall not affect the validity of the remaining portions of said ordinance or the Hudson Code of ordinances, as amended hereby, which shall remain in full force and effect.

SECTION 5. SAVINGS CLAUSE. An offense committed before the effective date of this ordinance is governed by prior law and the provisions of the Hudson Code of Ordinance, as amended, in effect when the offense was committed, and the former law is continued in effect for this purpose.

SECTION 6. PENALTY. Any person violating any of the provisions of this ordinance shall be deemed guilty of a misdemeanor and upon conviction thereof shall be fined in a sum not to exceed Five Hundred Dollars (\$500.00) and a separate offense shall be deemed committed upon each day during or on which a violation occurs or continues.

SECTION 7. EFFECTIVE DATE. This ordinance shall become effective from and after the date of its passage and final publication in the newspaper of record for the City of Hudson, Texas.

PASSED AND APPROVED this the 28th day of April 2023.

ATTEST

Cheryl Everett, City Secretary






Exhibit "A"

Appendix V, Tiny Houses to the International Residential Code, as approved by the International Code Council (ICC) and amended by the City of Hudson Council.

APPENDIX V TINY HOUSES SECTION AV101 GENERAL

AV101.1 Scope. This appendix shall be applicable to *tiny houses* used as single *dwelling units*. *Tiny houses* shall comply with the *International Residential Code* except as otherwise stated in this appendix.

SECTION AV102 DEFINITIONS **AV102.1 General.** The following words and terms shall, for the purposes of this appendix, have the meanings shown herein. Refer to Chapter 2 of the *International Residential Code* for general definitions.

EGRESS ROOF ACCESS WINDOW. A skylight or roof window designed and installed to satisfy the *emergency escape and rescue opening* requirements in Section R3 1 0.2.

LANDING PLATFORM. A landing measuring two treads deep and two risers tall, pro-vided as the top step of a stairway accessing a *loft*.

LOFT. Any floor level located above the main floor and open to it on at least one side, with a *ceiling height* less than 6 feet 8 inches (2032 mm), complying with the area, access, and guard requirements of Section AV104, and used as a living or sleeping space.

TINY HOUSE. A *dwelling* that is 400 or fewer square feet (37 m²) in floor area excluding *Lofts.* **Amended** For purposes of this ordinance, a "Tiny House" is defined as a principal residential dwelling that has a square footage of no less than two hundred forty (240) square feet and no greater than eight hundred (800) square ft.

SECTION AV103 CEILING HEIGHT

AV103.1 Minimum ceiling height. Habitable space and hallways in tiny houses shall have a ceiling height, not less than six feet eight inches (6ft 8"). Bathrooms, toilet rooms, and kitchens shall have a ceiling height not less than six feet four inches (6ft 4"). No obstructions shall extend below these minimum ceiling heights including beams, girders, ducts, lighting, or other obstructions.

Exception: Ceiling heights in lofts are permitted to be less than 6 feet 8 inches (2032 mm).

SECTION AV104 LOFTS

- **AV104.1 Minimum loft areas.** *Lofts* used as a sleeping or living space shall meet the minimum area and dimension requirements of Sections AV104.1.1 through AV104.1.3.
- **AV104.1.1 Minimum area.** Lofts shall have a floor area of not less than 35 square feet **AMENDED to** be: Lofts shall have a floor area of not less than 50 square feet.
- **AV104.1.2 Minimum dimensions.** *Lofts* shall be not less than 5 feet (1524 mm) in any horizontal dimension.
- **AV104.1.3 Height effect on loft area.** Portions of a *loft* with a sloping ceiling measuring less than 3 feet (914 mm) from the finished floor to the finished ceiling shall not be considered as contributing to the minimum required area for the loft.

Exception: Under gable roofs with a minimum slope of 6:12, portions of a *loft* with a sloping ceiling measuring less than 16 inches (406 mm) from the finished floor to the finished ceiling shall not be considered as contributing to the minimum required area for the loft.

- **AV104.2 Loft access.** The access to and primary egress from *lofts* shall be of any type described in Sections AV104.2. I through AV104.2.4
- **AV104.2.1 Stairways.** Stairways accessing *lofts* shall comply with this code or with Sections AV104.2.1.1 through AV104.2.1.5
- **AV104.2.1.1** Width. Stairways accessing a *loft* shall not be less than 17 inches (432 mm) in clear width at all points at or above the permitted handrail height. The minimum width below the handrail shall not be less than 20 inches (508 mm).
- **AV104.2.1.2 Headroom.** The headroom in stairways accessing a *loft* shall not be less than 6 feet 2 inches (1880 mm) measured vertically from the sloped line connecting the tread nosings in the middle of the tread width.

Exception: The headroom for *landing platforms* shall not be less than 4 feet 6 inches (1372mm).

AV.104.2.1.3 Treads and Risers. Risers for stairs accessing a *loft* shall be a minimum of 7 inches (178 mm) and a maximum of 12 inches (305 mm). Tread depth and riser height shall be calculated with the following formulas:

Tread depth= 20 inches (508 mm) minus 4/3 riser height

OR

Riser height= 15 inches (381 mm) minus 3/4 tread depth

Exception: Landing platforms shall measure two treads deep and two risers tall.

- **AV104.2.1.4 Handrails.** Handrails shall comply with Section R3 1 l. 7.8.
- AV104.2.1.5 Stairway guards. Guards at open sides of stairways shall comply with Section R312. 1.
- **AV104.2.2 Ladders.** Ladders accessing *lofts* shall comply with Sections AVI04.2.2. 1 and AVI 04.2.2.2
- **AV104.2.2.1 Size and capacity.** Ladders accessing *lofts* shall have 12 inches (305 mm) minimum rung width and 10 inches (254 mm) to 14 inches (356 mm) spacing between rungs. Ladders shall be capable of supporting a 200-pound (75 kg) load on any rung. Rung spacing shall be uniform within 3/8 inches (9.5 mm).
- AV104.2.2.2 Incline. Ladders shall be installed at 70 to 80 degrees from horizontal.
- **AV104.2.3 Alternating tread devices.** *Alternating tread devices* accessing *lofts* shall comply with Sections R3 11.7.11.1 and R311.7.1 1.2. The clear width at and below the handrails shall be not less than 20 inches (508 mm).
- **AV104.2.4 Ships ladders.** *Ships ladder* accessing *lofts* shall comply with Sections R311.7.12.1 and R311.7.12.2. The clear width at and below the handrails shall be not less than 20 inches (508 mm).

AV104.3 Loft guards. Loft guards shall be located along the open side(s) of *lofts* located more than 30 inches (762 mm) above the main floor. Loft guards shall be not less than 36 inches (914 mm) in height or one-half the clear height of the ceiling, whichever is less.

SECTION AV105 EMERGENCY ESCAPE AND RESCUE OPENINGS

AV105.1 General. *Tiny houses* shall meet the requirements of Section R310 for *emergency escape* and rescue openings.

Exception: Egress roof access windows in lofts used as sleeping rooms shall be deemed to meet the requirements of Section R310, where installed with the bottom of their opening no more than 44 inches (1118 mm) above the loft floor.